

CATERPILLAR RIGID DUMP TRUCKS 797F LAJ (2008 AND AFTER)



ENGINE C175-20 ACERT
Capacity: 417 liter

| USE | CLIMATE |
|----------------|---------------|
| Flexible (max) | Mediterranean |

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Check every 10 hours, change every 3 months/ 500 hours

| USE | CLIMATE |
|----------------|----------|
| Flexible (max) | Moderate |

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel MSP 15W-40

Check every 10 hours, change every 3 months/ 500 hours

DIFFERENTIAL REAR

Capacity: 1176 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

FINAL DRIVES REAR

Capacity: 184 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION + TORQUE CONVERTER

Capacity: 629 liter (System), Capacity: 303 liter (Torque converter sump)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Check every 10 hours, change every 6 months/ 1000 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

Check every 10 hours, change every 6 months/ 1000 hours

CATERPILLAR RIGID DUMP TRUCKS 797F LAJ (2008 AND AFTER)



GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

| USE | CLIMATE |
|------------|----------|
| Light Duty | Moderate |

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

WHEEL BEARINGS FRONT

Capacity: 61 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 1194 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant SP 17

Check every 10 hours, change every 48 months/ 6000 hours

BRAKE/HOIST SYSTEM

Capacity: 1850 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

Check every 10 hours, change every 2000 hours/ 12 months

CATERPILLAR RIGID DUMP TRUCKS 797F LAJ (2008 AND AFTER)



STEERING SYSTEM

Capacity: 360 liter (Hydraulic tank)

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 2000 hours/ 12 months

| USE | | CLIMATE |
|-------------------------------|-------------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| AgriDiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 2000 hours/ 12 months

| USE | | CLIMATE |
|---------------------------|--|----------|
| Biodegradable oil | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |

Check every 10 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.