CATERPILLAR BACKHOE LOADERS 430D BNK05900-> (2004-2006)



| SE | | CLIMATE |
|---|--|--|
| Preferred | | Mediterranean |
| PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40 | PRODUCT RECOMMENDATION 2 Dieselfleet CD+ 15W-40 | PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40 |
| Check every 10 hours, change every | 3 months/ 500 hours | |
| use Preferred | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 | PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40 | |
| Check every 10 hours, change every | 3 months/ 500 hours | |
| use Alternative (acceptable) | | climate Mediterranean |
| PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40 | PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40 | |
| Check every 10 hours, change every | 3 months/ 500 hours | ' |
| use Alternative (acceptable) | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Synfleet SHPD 10W-40 | PRODUCT RECOMMENDATION 2 Dieselfleet CD+ 15W-40 | PRODUCT RECOMMENDATION 3 Multifleet SHPD 10W-40 |
| Check every 10 hours, change every | 3 months/ 500 hours | |
| use Acceptable | | сымате Mediterranean |
| PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40 | PRODUCT RECOMMENDATION 2 Dieselfleet CD+ 15W-40 | PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40 |
| Check every 10 hours, change every | 250 hours/ 3 months | |
| use Acceptable | | climate Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |

CATERPILLAR BACKHOE LOADERS 430D BNK05900-> (2004-2006)



| DIFFERENTIAL FRONT POWERED AXLE Capacity: 7,5 liter | | | | |
|--|-------------------|--|--|--|
| | CLIMATE | | | |
| | Moderate | | | |
| PRODUCT RECOMMENDATION 2 | | | | |
| Gear Oil Alcat 50 | | | | |
| Check every 1 months/ 250 hours, change every 6 months/ 1000 hours | | | | |
| | CLIMATE | | | |
| | Arctic | | | |
| | AICIIC | | | |
| | Aiciic | | | |
| | Arctic | | | |
| | Gear Oil Alcat 50 | | | |

DIFFERENTIAL REAR 133-7234 FRICTION DISC

Capacity: 24 liter, Capacity: 1 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

| DIFFERENTIAL REAR 230-4017 BRAKE DISCS Capacity: 24 liter, Capacity: 0,15 liter (Special additive, only first fill) | | |
|---|---------------------------------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |
| Check every 1 months/ 250 hours, c | ange every 6 months/ 1000 hours | |

DIFFERENTIAL REAR STEERABLE AXLE

Capacity: 8,3 liter, Capacity: 0,45 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

CATERPILLAR BACKHOE LOADERS 430D BNK05900-> (2004-2006)



| FINAL DRIVES FRONT POWERED AXLE Capacity: 0,7 liter (each side) | | | |
|---|------------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | | |
| Check every 1 months/ 250 hours, change | every 6 months/ 1000 hours | | |
| USE | | CLIMATE | |
| Normal | | Arctic | |
| PRODUCT RECOMMENDATION 1 | | | |
| Gear Oil Alcat 10W | | | |
| Check every 1 months/ 250 hours, change | e every 6 months/ 1000 hours | | |

| FINAL DRIVES REAR STEERABLE AXLE Capacity: 1,6 liter (each side) | | |
|--|------------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Gearlube Racing 75W-140 | SP Gear 1011 | Syngear TDL 75W-90 |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| Capacity: 20 liter | | |
|-----------------------------------|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Check every 10 hours, change ever | y 6 months/ 1000 hours | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Check every 10 hours, change ever | ry 6 months/ 1000 hours | |

TRANSMISSION Powershift

CATERPILLAR BACKHOE LOADERS 430D BNK05900-> (2004-2006)



| TRANSMISSION + TORQUE CONVERTER Capacity: 19 liter (2WD), Capacity: 20,5 liter (4WD) | | |
|--|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Check every 10 hours, change every 6 months/ 1000 hours | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Check every 10 hours, change every 6 months/ 1000 hours | | |

| HYDRAULIC SYSTEM Capacity: 49 liter | | |
|--|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |

Check every 10 hours, change every 2000 hours/12 months

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40 | Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus |

Check every 10 hours, change every 2000 hours/12 months

| CLIMATE |
|----------|
| Moderate |
| |
| |
| |

PRODUCT RECOMMENDATION

CATERPILLAR BACKHOE LOADERS 430D BNK05900-> (2004-2006)



| COOLING SYSTEM Capacity: 23,6-25,5 liter | | |
|--|-------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 17 | | |
| Check every 10 hours, change every 36 i | nonths/3000 hours | |

Check every 10 hours, change every 36 months/ 3000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.