## CATERPILLAR WHEELED LOADERS 906 MER/CATERPILLAR 3034C (2003-2007)



| ENGINE 3044C DIT<br>Capacity: 10 liter |                          |               |  |
|--|--------------------------|---------------|--|
| USE                                    |                          | CLIMATE       |  |
| Preferred                              |                          | Mediterranean |  |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 |               |  |
| Agridiesel MSP 15W-40                  | Dieselfleet MSP 15W-40   |               |  |

Check every 10 hours, change every 500 hours/ 12 months

| USE                          |                            | CLIMATE                  |
|------------------------------|----------------------------|--------------------------|
| Preferred                    |                            | Moderate                 |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2   | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP Ultra FE 5W-30 | Agrisynth LSP Ultra 10W-40 | Agrisynth MSP 10W-40     |

Check every 10 hours, change every 500 hours/ 12 months

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40   | Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |

Check every 10 hours, change every 500 hours/ 12 months

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Agrisynth LSP 10W-40     | Multifleet SHPD 10W-40   |          |

Check every 10 hours, change every 500 hours/ 12 months

| USE                      | CLIMATE       |
|--------------------------|---------------|
| Alternative (acceptable) | Mediterranean |
| PRODUCT RECOMMENDATION 1 |               |
| Dieselfleet MSP 15W-40   |               |

Check every 10 hours, change every 500 hours/ 12 months

| Agrisynth LSP Ultra FE 5W-30 | Agrisynth LSP Ultra 10W-40 | Agrisynth MSP 10W-40     |
|------------------------------|----------------------------|--------------------------|
|                              |                            |                          |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2   | PRODUCT RECOMMENDATION 3 |
| Alternative (acceptable)     |                            | Moderate                 |
| USE                          |                            | CLIMATE                  |

Check every 10 hours, change every 500 hours/ 12 months

### DIFFERENTIAL FRONT

Capacity: 7,5 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR WHEELED LOADERS 906 MER/CATERPILLAR 3034C (2003-2007)



| DIFFERENTIAL REAR<br>Capacity: 8 liter |                                |                          |
|--|--------------------------------|--------------------------|
| USE                                    |                                | CLIMATE                  |
| Normal                                 |                                | Mediterranean            |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2       |                          |
| Gearlube GL-5 85W-140                  | Unigear LS GL-3/GL-5 85W-140   |                          |
| Check every 6 months/ 250 hours, chan  | ge every 12 months/ 1000 hours |                          |
| USE                                    |                                | CLIMATE                  |
| Normal                                 |                                | Moderate                 |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2       | PRODUCT RECOMMENDATION 3 |
| Gearlube Racing 75W-140                | SP Gear 1011                   | Syngear TDL 75W-90       |
| Check every 6 months/ 250 hours, chan  | ge every 12 months/ 1000 hours |                          |

#### **DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 7,5 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

|                                | CLIMATE  |
|--------------------------------|--|
|                                | Mediterranean  |
| PRODUCT RECOMMENDATION 2       |  |
| Unigear LS GL-3/GL-5 85W-140   |  |
| ge every 12 months/ 1000 hours |  |
|                                | CLIMATE  |
|                                | Moderate   |
| PRODUCT RECOMMENDATION 2       | PRODUCT RECOMMENDATION 3   |
| SP Gear 1011                   | Syngear TDL 75W-90   |
| ge every 12 months/ 1000 hours | -  |
|                                | Unigear LS GL-3/GL-5 85W-140  ge every 12 months/ 1000 hours  PRODUCT RECOMMENDATION 2 |

### **CATERPILLAR WHEELED LOADERS 906** MER/CATERPILLAR 3034C (2003-2007)



| HUB REDUCTIONS REAR Capacity: 0,7 liter |                                |                          |
|---|--------------------------------|--------------------------|
| USE                                     |                                | CLIMATE                  |
| Normal                                  |                                | Mediterranean            |
| PRODUCT RECOMMENDATION 1                | PRODUCT RECOMMENDATION 2       |                          |
| Gearlube GL-5 85W-140                   | Unigear LS GL-3/GL-5 85W-140   |                          |
| Check every 6 months/ 250 hours, char   | ge every 12 months/ 1000 hours |                          |
| USE                                     |                                | CLIMATE                  |
| Normal                                  |                                | Moderate                 |
| PRODUCT RECOMMENDATION 1                | PRODUCT RECOMMENDATION 2       | PRODUCT RECOMMENDATION 3 |
| Gearlube Racing 75W-140                 | SP Gear 1011                   | Syngear TDL 75W-90       |
| Check every 6 months/ 250 hours, char   | ge every 12 months/ 1000 hours |                          |

| TRANSMISSION HYDROSTATIC<br>Capacity: 1,2 liter |                                   |                          |
|---|-----------------------------------|--------------------------|
| USE   |                                   | CLIMATE                  |
| Normal  |                                   | Moderate                 |
| PRODUCT RECOMMENDATION 1                        | PRODUCT RECOMMENDATION 2          | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40                          | Dieselfleet CD+ 15W-40            | Multifleet SHPD 15W-40   |
| Check every 6 months/ 250 hours, ci             | hange every 12 months/ 1000 hours | '                        |

| HYDRAULIC SYSTEM Capacity: 49 liter (Hydraulic tank) |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                             | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40                               | Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |
| Check every 10 hours, change every                   | 2000 hours/ 12 months    | '                        |

| COOLING SYSTEM Capacity: 20 liter |                         |          |  |
|-----------------------------------|-------------------------|----------|--|
| USE                               |                         | CLIMATE  |  |
| Normal                            |                         | Moderate |  |
| PRODUCT RECOMMENDATION 1          |                         |          |  |
| Coolant SP 17                     |                         |          |  |
| Check every 10 hours, change ever | / 48 months/ 6000 hours |          |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.