

# CATERPILLAR WHEELED LOADERS 914G2

## KNP...1-213/CATERPILLAR C4.4 (2009 AND AFTER)



**ENGINE C4.4**  
Capacity: 7 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Dieselfleet LSP Ultra 10W-30</b>	<b>Dieselfleet MSP 10W-30</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agrisynth MSP 10W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra FE 5W-30</b>	<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Check every 10 hours, change every 3 months/ 500 hours*

### DIFFERENTIAL FRONT

Capacity: 15 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

### DIFFERENTIAL REAR

Capacity: 15 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR WHEELED LOADERS 914G2 KNP...1-213/CATERPILLAR C4.4 (2009 AND AFTER)

**TRANSMISSION HYDROSTATIC**

Capacity: 4 liter

USE		CLIMATE
Flexible (max)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

*Check every 1 months/ 250 hours, change every 3000 hours*

USE		CLIMATE
Flexible (max)		Cold
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Check every 1 months/ 250 hours, change every 3000 hours*

USE		CLIMATE
Flexible, fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

*Check every 500 hours*

USE		CLIMATE
Flexible, fluid analysis		Cold
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Check every 500 hours*

# CATERPILLAR WHEELED LOADERS 914G2

## KNP...1-213/CATERPILLAR C4.4 (2009 AND AFTER)



### HYDRAULIC SYSTEM

Capacity: 70 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 30</b>	<b>Gear Oil Alcat 30</b>	

*Check every 10 hours, change every 3000 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>AgriDiesel CRD+ 15W-40</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 10 hours, change every 3000 hours*

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		

*Check every 10 hours, change every 3000 hours*

### HYDRAULIC BRAKE SYSTEM

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Check every 1 months/ 250 hours*

### GREASE POINTS/NIPPLES DRIVE SHAFT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 1 months/ 250 hours*

### GREASE POINTS/NIPPLES OTHERS

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR WHEELED LOADERS 914G2 KNP...1-213/CATERPILLAR C4.4 (2009 AND AFTER)



## GREASE POINTS/NIPPLES STEERING COLUMN

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Check every 1 months/ 250 hours

## COOLING SYSTEM

Capacity: 23 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

Check every 10 hours, change every 72 months/ 12000 hours

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*