

# CATERPILLAR WHEELED LOADERS 950

## (1964-1984)



### ENGINE

| USE                           |                             | CLIMATE                       |
|-------------------------------|-----------------------------|-------------------------------|
| Normal                        |                             | Moderate                      |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |
| <i>Change every 250 hours</i> |                             |                               |

### DIFFERENTIAL FRONT + REAR

| USE                                                   |                          | CLIMATE  |
|-------------------------------------------------------|--------------------------|----------|
| Normal                                                |                          | Moderate |
| PRODUCT RECOMMENDATION 1                              | PRODUCT RECOMMENDATION 2 |          |
| <b>Gear Oil Alcat 30</b>                              | <b>Gear Oil Alcat 50</b> |          |
| <i>Check every 500 hours, change every 2000 hours</i> |                          |          |

| USE                                                   |  | CLIMATE |
|-------------------------------------------------------|--|---------|
| Normal                                                |  | Arctic  |
| PRODUCT RECOMMENDATION 1                              |  |         |
| <b>Gear Oil Alcat 10W</b>                             |  |         |
| <i>Check every 500 hours, change every 2000 hours</i> |  |         |

### TRANSMISSION Powershift

| USE                                                   |                          | CLIMATE       |
|-------------------------------------------------------|--------------------------|---------------|
| Normal                                                |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1                              | PRODUCT RECOMMENDATION 2 |               |
| <b>Gear Oil Alcat 30</b>                              | <b>Gear Oil Alcat 50</b> |               |
| <i>Check every 500 hours, change every 1000 hours</i> |                          |               |

| USE                                                   |  | CLIMATE |
|-------------------------------------------------------|--|---------|
| Normal                                                |  | Cold    |
| PRODUCT RECOMMENDATION 1                              |  |         |
| <b>Gear Oil Alcat 10W</b>                             |  |         |
| <i>Check every 500 hours, change every 1000 hours</i> |  |         |

### HYDRAULIC SYSTEM

| USE                                                   |                             | CLIMATE                     |
|-------------------------------------------------------|-----------------------------|-----------------------------|
| Normal                                                |                             | Moderate                    |
| PRODUCT RECOMMENDATION 1                              | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
| <b>Agridiesel CRD+ 15W-40</b>                         | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |
| <i>Check every 500 hours, change every 2000 hours</i> |                             |                             |

# CATERPILLAR WHEELED LOADERS 950

## (1964-1984)



### HYDRAULIC BRAKE SYSTEM

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

### BUCKET LOWER PINS

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

### GREASE POINTS/NIPPLES

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

### BUCKET LOWER PINS OIL LUBRICATED

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

### FINAL DRIVES FRONT + REAR

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |          |

*Check every 500 hours, change every 2000 hours*

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Arctic  |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

*Check every 500 hours, change every 2000 hours*

# CATERPILLAR WHEELED LOADERS 950

## (1964-1984)



### STEERING GEAR UNIT

| USE    |  | CLIMATE  |
|--------|--|----------|
| Normal |  | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |  |

| USE    |  | CLIMATE |
|--------|--|---------|
| Normal |  | Arctic  |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gear Oil Alcat 10W</b> |  |  |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*