

CATERPILLAR TELESCOPIC HANDLERS

RT/TH TH414C KEK/RWW S/N 00150 -> (2012 AND AFTER)



ENGINE C3.4B
Capacity: 8 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT

Capacity: 11,5 liter, Capacity: 0,35 liter (special additive)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 250 hours, change every 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 50 hours, change every 250 hours

DIFFERENTIAL REAR

Capacity: 11,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Check every 250 hours, change every 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Check every 50 hours, change every 250 hours

CATERPILLAR TELESCOPIC HANDLERS

RT/TH TH414C KEK/RWW S/N 00150 -> (2012 AND AFTER)

**HUB REDUCTIONS**

Capacity: 0,9 liter (all)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 250 hours, change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 50 hours, change every 250 hours***TRANSFERBOX**

Capacity: 2,8 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50*Check every 250 hours, change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 250 hours, change every 1000 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50*Change every 250 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Change every 250 hours*

CATERPILLAR TELESCOPIC HANDLERS

RT/TH TH414C KEK/RWW S/N 00150 -> (2012 AND AFTER)



TRANSMISSION Powershift
Capacity: 14 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 10 hours, change every 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 1000 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 10 hours, change every 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 250 hours

HYDRAULIC SYSTEM

Capacity: 90 liter (Hydraulic tank), Capacity: 145 liter (Total)

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES BOOM SLIDING SURFACES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

Check every 50 hours

CATERPILLAR TELESCOPIC HANDLERS

RT/TH TH414C KEK/RWW S/N 00150 -> (2012 AND AFTER)



GREASE POINTS/NIPPLES DRIVE SHAFT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease*Check every 500 hours*

GREASE POINTS/NIPPLES OTHERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease*Check every 50 hours*

COOLING SYSTEM

Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Check every 10 hours, change every 72 months/ 12000 hours*

AIRCONDITIONING SYSTEM

Capacity: 1,35 kg

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.