

ENGINE 3306 Capacity: 30 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 1	months/ 250 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	
Check every 10 hours, change every 1	months/ 250 hours	

HYDRAULIC SYSTEM Capacity: 185 liter (Hydraulic tank), Ca	apacity: 400 liter (System)		
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 2000 hours/ 12 months

USE	CLIMATE
Biodegradable oil	Moderate
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	

Check every 10 hours, change every 2000 hours/ 12 months

COOLING SYSTEM Capacity: 81,5 liter, Capacity: 4,5 liter (Reservoir)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every 72 months/ 12000 hours		



BRAKE SYSTEM WET BRAKES Capacity: 0,95 liter (each)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours, cl	hange every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Check every 1 months/ 250 hours, cl	nange every 12 months/ 2000 hours	

SWING GEAR Capacity: 28,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 2000 hours/ 12 mon	ths	



SWING REDUCTION UNIT Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		
TANDEM DRIVE UNIT		
Capacity: 159 liter		
USE		CLIMATE Moderate
Normal		Moderate
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	e every 12 months/ 2000 hours	



TRAVEL REPUBLICATION UNIT		
TRAVEL REDUCTION UNIT Capacity: 14 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 1 months/ 250 hours, ch	nange every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90
Check every 1 months/ 250 hours, ch	nange every 12 months/ 2000 hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Change every 250 hours	·	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90
Change every 250 hours	·	
WHEEL BEARINGS		
Capacity: 13,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 500 hours/ 3 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

MoS2 Grease EP 2

Change every 250 hours