CATERPILLAR ASPHALT PAVERS AP/BG AP-650B A7P



ENGINE Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Change every 250 hours		·
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	
Change every 250 hours		

HUB REDUCTIONS Capacity: 3,2 liter (each hub)	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
Change every 500 hours	

PUMP DRIVE HYDROSTATIC TRA Capacity: 2,6 liter	NSMISSION		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		

CATERPILLAR ASPHALT PAVERS AP/BG AP-650B A7P



HYDRAULIC SYSTEM Capacity: 170 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 1000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid HT-Plus
Change every 1000 hours		

COOLING SYSTEM Capacity: 18 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Change every 12000 hours/ 72 months	

REDUCTION UNITS AUGER ASSEMBLY AND CONVEYOR(S) Capacity: 0,7-1 liter (each side)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Change every 500 hours	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.