PRODUCT RECOMMENDATION

CATERPILLAR ASPHALT PAVERS AP/BG AP-655C AYP, CDG

ENGINE
Capacity: 14,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrisynth LSP 10W-40	**Agridiesel CRD+ 15W-40**	**Kroontrak MTH 10W-30**

Change every 250 hours

HUB REDUCTIONS
Capacity: 4,2 liter (each hub)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Change every 500 hours

PUMP DRIVE HYDROSTATIC TRANSMISSION
Capacity: 2,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR ASPHALT PAVERS AP/BG AP-655C AYP, CDG

HYDRAULIC SYSTEM
Capacity: 151 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Change every 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	**Agridiesel CRD+ 15W-40**	**Agrifluid HT-Plus**

Change every 1000 hours

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

COOLING SYSTEM
Capacity: 35,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Change every 12000 hours/ 72 months

REDUCTION UNITS AUGER ASSEMBLY AND CONVEYOR(S)
Capacity: 0,6 liter (each side)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**	

Change every 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	**Gearlube GL-5 80W-90**	**Unigear HS GL-3/GL-5 80W-90**

Change every 500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR ASPHALT PAVERS AP/BG AP-655C AYP, CDG

TRACK ROLLERS Capacity: 160 CM3		
USE Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 **Multifleet SCD 40**		
Check every 500 hours, change every 2000 hours		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Multifleet SCD 30**		
Check every 500 hours, change every 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367