

# CATERPILLAR TRACKED EXCAVATORS

## 235 83X (1973-1986)

**ENGINE**

Capacity: 27 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 250 hours/ 1 months*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40***Change every 250 hours/ 1 months*

## USE

Normal

## CLIMATE

Cold

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Change every 250 hours/ 1 months***FINAL DRIVES**

Capacity: 53 liter (each side)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30****HYDRAULIC SYSTEM**

Capacity: 329 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

# CATERPILLAR TRACKED EXCAVATORS

## 235 83X (1973-1986)



### GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

### COOLING SYSTEM

Capacity: 44 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 17***Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

### CLAMSHELL ROTATOR GEAR DRIVE

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

### PUMP DRIVE

Capacity: 6,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 2000 hours/ 12 months*

### SWING GEAR

Capacity: 38 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Check every 12 months/ 2000 hours*

# CATERPILLAR TRACKED EXCAVATORS

## 235 83X (1973-1986)



### SWING REDUCTION UNIT

Capacity: 34 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

Check every 1 months/ 250 hours

### TRACK PINS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

### TRACK ROLLERS & IDLERS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.