

ENGINE Mitsubishi 4M40-TL Capacity: 7,2 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 250 hours/ 1 months		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 100 hours		

FINAL DRIVES Capacity: 1,7 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
Change every 2000 hours/ 12 months	
USE	CLIMATE
Normal	 Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Change every 2000 hours/ 12 months

USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

Change every 2000 hours/ 12 months

USE	CLIMATE
Initial service	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
Change every 250 hours	



USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		
HYDRAULIC SYSTEM Capacity: 57 liter (Reservoir), Capacity: 94	liter (System)	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 250 hours		
USE		CLIMATE
50% use of breaker		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 1000 hours		
USE		CLIMATE
100% use of breaker		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 600 hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		



COOLING SYSTEM Capacity: 1,5 liter (Reservoir), Capacity: 15 liter (System)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Champe avery 24 manths (2000 haver		

Change every 24 months/ 3000 hours

SWING GEAR Capacity: 4,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

SWING REDUCTION UNIT		
Capacity: 1,5 liter USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 1000 hours/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 1000 hours/ 6 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 1000 hours/ 6 months		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 250 hours	1	



USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		
TRACK IDLERS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Check every 500 hours, change every 200	0 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 500 hours, change every 2000 hours

CATERPILLAR TRACKED EXCAVATORS 307B 7DZ (1999-2004)



IRACK ROLLERS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 500 hours, change every 200	0 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 500 hours, change every 200	0 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 500 hours, change every 200	0 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.