

| ENGINE 3116T Capacity: 20,5 liter | | |
|--------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |
| Change every 250 hours/ 1 months | | · · · |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 | |
| Change every 250 hours/ 1 months | | |
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |
| Change every 100 hours | | i |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 | |
| Change eveny 100 hours | • | |

Change every 100 hours



| | CLIMATE |
|-------------------------------|---|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 50 | |
| e every 12 months/ 2000 hours | |
| | CLIMATE |
| | Arctic |
| | |
| | |
| every 12 months/ 2000 hours | |
| | CLIMATE |
| | Moderate |
| PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 50 | |
| | |
| | CLIMATE |
| | Arctic |
| | |
| | |
| | |
| | |
| 20 liter (System) | |
| | CLIMATE |
| | Mediterranean |
| | |
| | |
| | |
| | Gear Oil Alcat 50 e every 12 months/ 2000 hours e every 12 months/ 2000 hours PRODUCT RECOMMENDATION 2 |

| USE | | CLIMATE |
|----------------------------------|--------------------------|---------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Agrifluid Synth XHP Ultra |
| Change avery 2000 hours/ 12 mont | ha | I |

Change every 2000 hours/ 12 months



| PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 1000 hours CLIMATE JUSE CLIMATE 50% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra Change every 1000 hours USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 Mediterranean Gear Oil Alcat 30 CLIMATE Change every 600 hours USE USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30 CLIMATE 100% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agrificiesel CRD+ 15W-40 Agrificied Synth XHP Ultra | USE | | CLIMATE |
|--|--------------------------|--------------------------|---------------------------|
| Gear Oil Alcat 30 Climate Change every 1000 hours CLIMATE S0% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra Change every 1000 hours USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 Mediterranean Gear Oil Alcat 30 CLIMATE Change every 600 hours CLIMATE USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 OWA use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 OWA use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 OWA use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | 50% use of breaker | | Mediterranean |
| Change every 1000 hours USE CLIMATE 50% use of breaker PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra Change every 1000 hours USE CLIMATE 100% use of breaker PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 600 hours USE CLIMATE 100% use of breaker PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 600 hours USE CLIMATE 100% use of breaker PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 CLIMATE 100% use of breaker PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | PRODUCT RECOMMENDATION 1 | | |
| USE CLIMATE Moderate Moderate CLIMATE Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra Change every 1000 hours USE CLIMATE Mediterranean Mediterranean Mediterranean Change every 600 hours USE CLIMATE Mediterranean Change every 600 hours USE CLIMATE Moderate PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 600 hours USE CLIMATE Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agrifluid Synth XHP Ultra CLIMATE Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra CLIMATE MODERATE MODERATE MODERATE PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agrifluid Synth XHP Ultra CLIMATE MODERATE PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra CLIMATE MODERATE PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra CLIMATE MODERATE PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra CLIMATE MODERATE PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra CLIMATE MODERATE PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra CLIMATE MODERATE PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra CLIMATE MODERATE PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra Agr | Gear Oil Alcat 30 | | |
| So% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-400 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra Change every 1000 hours CLIMATE USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 Mediterranean Gear Oil Alcat 30 CLIMATE Change every 600 hours CLIMATE USE CLIMATE 100% use of breaker Moderate | Change every 1000 hours | | |
| PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra Change every 1000 hours CLIMATE USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 600 hours CLIMATE USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 Change every 600 hours Change every 600 hours E USE CLIMATE 100% use of breaker PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | USE | | CLIMATE |
| Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra Change every 1000 hours USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 600 hours CLIMATE USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 CLIMATE Gear Oil Alcat 30 CLIMATE Change every 600 hours CLIMATE USE CLIMATE 100% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra Agrifluid Synth XHP Ultra | 50% use of breaker | | Moderate |
| Change every 1000 hours CLIMATE USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 Mediterranean Gear Oil Alcat 30 Climate Change every 600 hours Climate USE CLIMATE 100% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Of the product recommendation 2 PRODUCT RECOMMENDATION 3 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| USE CLIMATE 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 Mediterranean Gear Oil Alcat 30 CLIMATE Change every 600 hours CLIMATE USE CLIMATE 100% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Agrifluid Synth XHP Ultra |
| 100% use of breaker Mediterranean PRODUCT RECOMMENDATION 1 Mediterranean Gear Oil Alcat 30 Climate Change every 600 hours CLIMATE USE CLIMATE 100% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | Change every 1000 hours | | |
| PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 600 hours USE CLIMATE 100% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | USE | | CLIMATE |
| Gear Oil Alcat 30 Climate Change every 600 hours CLIMATE Use CLIMATE 100% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | 100% use of breaker | | Mediterranean |
| Change every 600 hours USE CLIMATE 100% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | PRODUCT RECOMMENDATION 1 | | |
| USE CLIMATE 100% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | Gear Oil Alcat 30 | | |
| 100% use of breaker Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | Change every 600 hours | | |
| PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | USE | | CLIMATE |
| Kroontrak CVT 10W-40 Agridiesel CRD+ 15W-40 Agrifluid Synth XHP Ultra | 100% use of breaker | | Moderate |
| | PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Change every 600 hours | Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Agrifluid Synth XHP Ultra |
| | Change every 600 hours | | |
| | | | |

| GREASE POINTS/NIPPLES | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| MoS2 Grease EP 2 | |

| COOLING SYSTEM Capacity: 1,5 liter (Reservoir), Capacity: 20 liter (System) | | | |
|--|--|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| Coolant SP 17 | | | |
| Change over 6000 hours 72 months | | | |

Change every 6000 hours/ 72 months



| SWING GEAR Capacity: 15,2 liter | | |
|------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 12 months/ 2000 hours

| SWING REDUCTION UNIT Capacity: 6 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Check every 1 months/ 250 hours, change every 6 months/ 1000 hours | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |

Gear Oil Alcat 10W

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Change every 250 hours

| USE | CLIMATE |
|--------------------------|---------|
| Initial service | Arctic |
| PRODUCT RECOMMENDATION 1 | |
| Gear Oil Alcat 10W | |
| Change every 250 hours | · |

 TRACK IDLERS

 USE
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 Image: Climate

 Multifleet SCD 30
 Image: Climate



| TRACK ROLLERS | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Multifleet SCD 30 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.