

CATERPILLAR TRACKED EXCAVATORS

325B ABD (1995-2002)



ENGINE 3116T
Capacity: 21,5 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 1 months/ 250 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|-------------------------------|--|
| Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 | |

Check every 10 hours, change every 1 months/ 250 hours

FINAL DRIVES

Capacity: 10 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gear Oil Alcat 10W | | |

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Change every 250 hours

| USE | CLIMATE |
|-----------------|---------|
| Initial service | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gear Oil Alcat 10W | | |

Change every 250 hours

HYDRAULIC SYSTEM

Capacity: 141 liter (Hydraulic tank), Capacity: 265 liter (System)

CATERPILLAR TRACKED EXCAVATORS

325B ABD (1995-2002)



| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 2000 hours/ 12 months

| USE | | CLIMATE |
|-----------------------------|-------------------------------|----------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Agrifluid Synth XHP Ultra |

Check every 10 hours, change every 2000 hours/ 12 months

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Up to 50% hammer use | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 1000 hours/ 12 months

| USE | | CLIMATE |
|-----------------------------|-------------------------------|----------------------------------|
| Up to 50% hammer use | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Agrifluid Synth XHP Ultra |

Check every 10 hours, change every 1000 hours/ 12 months

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Continuous hammer use | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 600 hours/ 12 months

| USE | | CLIMATE |
|-----------------------------|-------------------------------|----------------------------------|
| Continuous hammer use | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Agrifluid Synth XHP Ultra |

Check every 10 hours, change every 600 hours/ 12 months

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| HT Q9 High Grade Grease | Labora Grease | |

Change every 10 hours

CATERPILLAR TRACKED EXCAVATORS

325B ABD (1995-2002)

**COOLING SYSTEM**

Capacity: 31,5 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 17 | | |

Check every 10 hours, change every 72 months/ 6000 hours

SWING GEAR

Capacity: 18,7 liter

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 2000 hours/ 12 months

SWING REDUCTION UNIT

Capacity: 8 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Change every 250 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Change every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

CATERPILLAR TRACKED EXCAVATORS

325B ABD (1995-2002)



information contained herein is subject to changes without notification.