

# CATERPILLAR WHEELED EXCAVATORS

## 224B

**ENGINE**

Capacity: 15 liter

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Multifleet SCD 40</b> | <b>Multifleet SCD 30</b> |               |

*Change every 250 hours/ 1 months*

| USE                         |                             | CLIMATE                       |
|-----------------------------|-----------------------------|-------------------------------|
| Normal                      |                             | Moderate                      |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Change every 250 hours/ 1 months*

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Cold    |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Multifleet SCD 10W</b> |  |         |

*Change every 250 hours/ 1 months***DIFFERENTIAL STEERED AXLE**

Capacity: 10,5 liter

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gearlube LS 80W-90</b> |  |          |

*Check every 500 hours, change every 1000 hours***HUB REDUCTIONS**

Capacity: 2,5 liter (each hub)

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gearlube LS 80W-90</b> |  |          |

*Change every 1000 hours/ 12 months*

# CATERPILLAR WHEELED EXCAVATORS

## 224B



### TRANSAXLE

Capacity: 13,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 1000 hours/ 12 months*

### HYDRAULIC SYSTEM

Capacity: 390 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 2000 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Change every 2000 hours/ 12 months*

### GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

### COOLING SYSTEM

Capacity: 30 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 17***Change every 2000 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.