

CATERPILLAR WHEELED EXCAVATORS

M322C BDK (2005 AND AFTER)

**ENGINE**

Capacity: 16 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Change every 500 hours/ 3 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agrisynth MSP 10W-40	Armado Synth 10W-40

*Change every 500 hours/ 3 months***DIFFERENTIAL FRONT**

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Change every 1000 hours/ 6 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

*Check every 1 months/ 250 hours, change every 500 hours***DIFFERENTIAL REAR**

Capacity: 14,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Change every 1000 hours/ 6 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Check every 1 months/ 250 hours, change every 500 hours

CATERPILLAR WHEELED EXCAVATORS

M322C BDK (2005 AND AFTER)



HUB REDUCTIONS

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Change every 1000 hours/ 6 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Check every 1 months/ 250 hours, change every 500 hours

TRANSMISSION

Capacity: 2,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Change every 1000 hours/ 6 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Change every 1000 hours/ 6 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 1 months/ 250 hours, change every 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 1 months/ 250 hours, change every 500 hours

HYDRAULIC SYSTEM

Capacity: 350 liter (System), Capacity: 255 liter (Tank)

CATERPILLAR WHEELED EXCAVATORS

M322C BDK (2005 AND AFTER)



USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Change every 2000 hours/ 12 months

USE		CLIMATE
50% use of breaker		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Change every 1000 hours

USE		CLIMATE
50% use of breaker		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Change every 1000 hours

USE		CLIMATE
100% use of breaker		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Change every 600 hours

USE		CLIMATE
100% use of breaker		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Change every 600 hours

COOLING SYSTEM

Capacity: 40 liter

USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 500 hours, change every 36 months/ 6000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

CATERPILLAR WHEELED EXCAVATORS M322C BDK (2005 AND AFTER)



inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.