

CATERPILLAR MOTOR GRADERS 120H 2AN

(1995-2005)



ENGINE 3116T
Capacity: 20 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 1 months/ 250 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gear Oil Alcat 30	Gear Oil Alcat 50

Check every 10 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

Check every 10 hours, change every 6 months/ 1000 hours

TANDEM DRIVE

Capacity: 61 liter (each side)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gear Oil Alcat 30	Gear Oil Alcat 50

Check every 100 hours, change every 2000 hours/ 24 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

Check every 100 hours, change every 2000 hours/ 24 months

CATERPILLAR MOTOR GRADERS 120H 2AN (1995-2005)



TRANSMISSION

Capacity: 34 liter (+ differential)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 10 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM

Capacity: 38 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 100 hours, change every 4000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Check every 100 hours, change every 4000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Change every 100 hours

USE		CLIMATE
Light Duty		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

Change every 100 hours

CATERPILLAR MOTOR GRADERS 120H 2AN (1995-2005)



WHEEL SPINDLE BEARING FRONT

Capacity: 0,5 liter (each side)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 100 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 100 hours, change every 2000 hours/ 24 months

COOLING SYSTEM

Capacity: 43 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 72 months/ 12000 hours

CIRCLE DRIVE GEARBOX

Capacity: 7 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 2000 hours/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.