## CATERPILLAR MOTOR GRADERS 140H 8KM (1994-1996)



ENGINE 3306 Capacity: 29 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 1 m	nonths/ 250 hours	'
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40
Check every 10 hours, change every 1 m	nonths/ 250 hours	
USE		CLIMATE
Normal, fuel with sulfur content > $1$	,5% by weight	Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 1 m	nonths/ 125 hours	
USE		CLIMATE
Normal, fuel with sulfur content > 1,5% by weight		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40
Check every 10 hours, change every 1 m	nonths/ 125 hours	

<b>TANDEM DRIVE</b> Capacity: 64 liter (each side)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 12 months/ 2000 hours	

## CATERPILLAR MOTOR GRADERS 140H 8KM (1994-1996)



Capacity: 47 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Charle avenu 1 months/250 hours shange	avery 6 months/ 1000 hours	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM Capacity: 38 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Asyntho 5W-30

Check every 10 hours, change every 2000 hours/ 12 months

WHEEL SPINDLE BEARING FRONT   Capacity: 0,5 liter (each wheel)   USE CLIMATE
USE CLIMATE
Normal Mediterranean
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2
Gear Oil Alcat 30 Gear Oil Alcat 50
Check every 3 months/ 500 hours
USE CLIMATE
Normal Cold
PRODUCT RECOMMENDATION 1
Gear Oil Alcat 10W

Check every 3 months/ 500 hours

## CATERPILLAR MOTOR GRADERS 140H 8KM (1994-1996)



COOLING SYSTEM Capacity: 45 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 24 months/ 3000 hours

CIRCLE DRIVE GEARBOX Capacity: 7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.