

CATERPILLAR ARTICULATED DUMP TRUCKS 740 AXM (TILL 2008)



ENGINE 3406E ATAAC
Capacity: 38 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Change every 250 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

Change every 250 hours

DIFFERENTIAL CENTRE
Capacity: 73,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 50

Check every 500 hours, change every 2000 hours

DIFFERENTIAL FRONT
Capacity: 75 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 50

Check every 500 hours, change every 2000 hours

DIFFERENTIAL REAR
Capacity: 73,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 50

Check every 500 hours, change every 2000 hours

CATERPILLAR ARTICULATED DUMP TRUCKS 740 AXM (TILL 2008)



FINAL DRIVES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Check every 500 hours, change every 2000 hours

TRANSFERBOX

Capacity: 21 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 500 hours, change every 1000 hours

TRANSMISSION + TORQUE CONVERTER

Capacity: 36 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 500 hours, change every 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 500 hours, change every 1000 hours

COOLING SYSTEM

Capacity: 80 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

CATERPILLAR ARTICULATED DUMP TRUCKS 740 AXM (TILL 2008)



BRAKE/HOIST SYSTEM

Capacity: 233 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

STEERING SYSTEM

Capacity: 97 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Change every 1000 hours/ 6 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.