

DOOSAN (DAEWOO) WHEELED EXCAVATORS SOLAR/DH SOLAR 130W-V DEAWOO DB58T (1999-2003)

**ENGINE** Daewoo DB58T

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 150 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 50 hours

DIFFERENTIAL HUB REDUCTIONS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 250 hours/ 6 months

DIFFERENTIAL HUB REDUCTIONS REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 250 hours/ 6 months

DOOSAN (DAEWOO) WHEELED EXCAVATORS SOLAR/DH SOLAR 130W-V DEAWOO DB58T (1999-2003)



TRANSMISSION Powershift

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	

Change every 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	

Change every 50 hours

HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 1000 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 1000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

DOOSAN (DAEWOO) WHEELED EXCAVATORS SOLAR/DH SOLAR 130W-V DEAWOO DB58T (1999-2003)

**SWING REDUCTION UNIT**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 250 hours/ 6 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.