

DOOSAN (DAEWOO) WHEELED LOADING SHOVEL/DOZER MEGA MEGA 160 TC

DAEWOO DB58S (2000-2008)



ENGINE Daewoo DB58S
Capacity: 13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 200 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL FRONT
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Change every 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Change every 250 hours/ 6 months

DIFFERENTIAL REAR
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Change every 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Change every 250 hours/ 6 months

DOOSAN (DAEWOO) WHEELED LOADING SHOVEL/DOZER MEGA MEGA 160 TC

DAEWOO DB58S (2000-2008)



HUB REDUCTIONS FRONT

Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 1500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 250 hours/ 6 months*

HUB REDUCTIONS REAR

Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 1500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 250 hours/ 6 months*

TRANSMISSION POWERSHIFT ZF 4WG130 4/3

Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Change every 250 hours/ 6 months*

DOOSAN (DAEWOO) WHEELED LOADING SHOVEL/DOZER MEGA MEGA 160 TC DAEWOO DB58S (2000-2008)



HYDRAULIC SYSTEM

Capacity: 100 liter (Tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46*Change every 2000 hours*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 29 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Change every 1000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.