

# JCB SKID STEER LOADERS 300 JCB DIESELMAX TC-68 T4I (1745010 ->) (2012-2015)



**ENGINE** JCB Dieselmex TC-68  
Capacity: 12-15 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 6 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2   |  |
|-----------------------------|----------------------------|--|
| <b>Agrisynth LSP 10W-40</b> | <b>Armado Synth 10W-40</b> |  |

*Check every 10 hours, change every 500 hours/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Check every 10 hours, change every 6 months/ 250 hours*

| USE    | CLIMATE |
|--------|---------|
| Severe | Arctic  |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2   |  |
|-----------------------------|----------------------------|--|
| <b>Agrisynth LSP 10W-40</b> | <b>Armado Synth 10W-40</b> |  |

*Check every 10 hours, change every 6 months/ 250 hours*

## HYDRAULIC SYSTEM

Capacity: 26 liter (Hydraulic tank), Capacity: 30 liter (System)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
|---------------------------|--------------------------|---------------------------|
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>       | <b>Perlus Biosynth 32</b> |

*Check every 10 hours, change every 2000 hours/ 24 months*

| USE               | CLIMATE  |
|-------------------|----------|
| Biodegradable oil | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

*Check every 10 hours, change every 2000 hours/ 24 months*

# JCB SKID STEER LOADERS 300 JCB DIESELMAX TC-68 T4I (1745010 ->) (2012-2015)



## GREASE POINTS/NIPPLES

| USE                            |                          | CLIMATE                         |
|--------------------------------|--------------------------|---------------------------------|
| Normal                         |                          | Moderate                        |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3        |
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> |

## COOLING SYSTEM

Capacity: 22 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 10 hours, change every 2000 hours/ 24 months*

## CHAIN CASE

Capacity: 23,3 liter

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 50 hours, change every 1000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*