JCB TELESCOPIC HANDLERS 527-58 (81 KW) STAGE IIIB/T4I (2014 AND AFTER)



ENGINE JCB Ecomax T4i Capacity: 15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| DIFFERENTIAL FRONT Capacity: 17,7 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT | |
| | |

Check every 50 hours, change every 6 months/ 500 hours

| DIFFERENTIAL REAR Capacity: 10 liter | | |
|---|-----------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 50 hours, change every 6 mo | nths/ 500 hours | |

| HUB REDUCTIONS FRONT Capacity: 1,9 liter (each hub) | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT | |
| | |

Check every 1 months/ 100 hours, change every 12 months/ 1000 hours

| HUB REDUCTIONS REAR Capacity: 2 liter (each hub) | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 1 months/ 100 hours, change | every 12 months/ 1000 hours | |

JCB TELESCOPIC HANDLERS 527-58 (81 KW) STAGE IIIB/T4I (2014 AND AFTER)



| TRANSMISSION Synchro Shuttle SS700/750 Capacity: 11,5 liter (Change capacity), Capacity: 13,5 liter (Dry fill) | | |
|--|------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |
| Check every 10 hours, change every 1000 | hours/ 12 months | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Charles avery 10 hours about avery 1000 | have 12 manuths | |

Check every 10 hours, change every 1000 hours/ 12 months

| TRANSMISSION POWERSHIFT PS760 Capacity: 21 liter (Change capacity), Capacity: 23 liter (Dry fill) | | |
|--|--|---------------|
| USE CLIMATE | | |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 1000 hours/ 12 months

| USE | | CLIMATE |
|--------------------------|---|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| 0k k | h | • |

Check every 10 hours, change every 1000 hours/ 12 months

| use climate Normal Tropical | PRODUCT RECOMMENDATION 1 Perlus H 46 | PRODUCT RECOMMENDATION 2 Perlus AF 46 | |
|--|--|--|--|
| | | | |
| HYDRAULIC SYSTEM Capacity: 116 liter (Hydraulic tank) | HYDRAULIC SYSTEM Capacity: 116 liter (Hydraulic tank) | | |

Check every 50 hours, change every 2000 hours/24 months

| Perlus H 32 | Perlus AF 32 | |
|--------------------------|--------------------------|----------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Normal | | Moderate |
| USE | | CLIMATE |

Check every 50 hours, change every 2000 hours/24 months

JCB TELESCOPIC HANDLERS 527-58 (81 KW) STAGE IIIB/T4I (2014 AND AFTER)



| HYDRAULIC BRAKE SYSTEM | | |
|--------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 15 | | |
| | | |

Check every 10 hours, change every 2000 hours/24 months

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Preferred | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| HT Q9 High Grade Grease | Labora Grease | |

| COOLING SYSTEM Capacity: 28 liter | | |
|--------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |
| Check every 10 hours, change every 2 | 000 hours/ 24 months | · |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.