JCB TELESCOPIC HANDLERS TM270 PERKINS 1004-4LR2 (1996-2004)



ENGINE Capacity: 10,7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 1000 hours		·
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 100 hours	·	

DIFFERENTIAL Capacity: 20 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 1000 hours	

Capacity: 1,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

TRANSFERBOX

Change every 100 hours

JCB TELESCOPIC HANDLERS TM270 PERKINS 1004-4LR2 (1996-2004)



TRANSMISSION Capacity: 13 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF-F (Ford)		

HYDRAULIC SYSTEM Capacity: 90 liter	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 2000 hours	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 2000 hours	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 15,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.