

JCB TRACKED EXCAVATORS JS-330 L

ISUZU AH-6HK1X STAGE IIIA/T3 (2006-2012)



ENGINE Isuzu AH-6HK1X
Capacity: 38 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Change every 250 hours/ 1 months

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Change every 100 hours

HYDRAULIC SYSTEM

Capacity: 320 liter (Hydraulic system including tank), Capacity: 152 liter (Hydraulic tank)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Perlus Biosynth 46

PRODUCT RECOMMENDATION 2
Perlus H 46

PRODUCT RECOMMENDATION 3
Perlus H 68

Change every 2000 hours/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus Biosynth 32

PRODUCT RECOMMENDATION 2
Perlus H 32

Change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
HT Q9 High Grade Grease

PRODUCT RECOMMENDATION 2
Labora Grease

SWING GEARBOX GREASE PACKING

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
HT Q9 High Grade Grease

PRODUCT RECOMMENDATION 2
Labora Grease

JCB TRACKED EXCAVATORS JS-330 L

ISUZU AH-6HK1X STAGE IIIA/T3 (2006-2012)



SWING REDUCTION UNIT

Capacity: 14,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 1000 hours/ 6 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 2 months/ 100 hours*

SWING RING GEAR TEETH

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

PRODUCT RECOMMENDATION 2

Labora Grease

TRACK IDLERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 2000 hours*

TRACK ROLLERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 2000 hours*

JCB TRACKED EXCAVATORS JS-330 L

ISUZU AH-6HK1X STAGE IIIA/T3 (2006-2012)

**TRAVEL REDUCTION UNIT**

Capacity: 8,5 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 1000 hours/ 6 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 2 months/ 100 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.