

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U U17-3A KUBOTA D902 (2008 AND AFTER)



ENGINE Kubota D902
Capacity: 3,6 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 50

Check every 10 hours, change every 500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40

Check every 10 hours, change every 500 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20

Check every 10 hours, change every 500 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Check every 10 hours, change every 500 hours

HYDRAULIC SYSTEM

Capacity: 21 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 68

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus H 32

Check every 10 hours, change every 1000 hours

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U U17-3A KUBOTA D902 (2008 AND AFTER)



USE		CLIMATE
20-40% Hydraulic hammer use		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
<i>Check every 10 hours, change every 800 hours</i>		
USE		CLIMATE
20-40% Hydraulic hammer use		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	
<i>Check every 10 hours, change every 800 hours</i>		
USE		CLIMATE
40-60% Hydraulic hammer use		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
<i>Check every 10 hours, change every 400 hours</i>		
USE		CLIMATE
40-60% Hydraulic hammer use		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	
<i>Check every 10 hours, change every 400 hours</i>		
USE		CLIMATE
60-80% Hydraulic hammer use		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
<i>Check every 10 hours, change every 300 hours</i>		
USE		CLIMATE
60-80% Hydraulic hammer use		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	
<i>Check every 10 hours, change every 300 hours</i>		
USE		CLIMATE
80-100% Hydraulic hammer use		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
<i>Check every 10 hours, change every 200 hours</i>		

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U U17-3A KUBOTA D902 (2008 AND AFTER)



USE		CLIMATE
80-100% Hydraulic hammer use		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	
<i>Check every 10 hours, change every 200 hours</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM		
Capacity: 2,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
<i>Check every 10 hours, change every 24 months</i>		

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U U17-3A KUBOTA D902 (2008 AND AFTER)



TRAVEL REDUCTION UNIT

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Change every 500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 500 hours

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.