KUBOTA TRACKED EXCAVATORS K/KH/KX/U U20-3A



ENGINE Capacity: 4,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SHPD 15W-40	
Change every 250 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SHPD 15W-40	
Change avery EQ hours	

Change every 50 hours

HYDRAULIC SYSTEM Capacity: 37 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
	1	1

Change every 1000 hours

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	

Change every 1000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 1000 hours	1	1

 GREASE POINTS/NIPPLES

 USE
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2
 PRODUCT RECOMMENDATION 3

 Labora Grease
 Q5 MP Calcep Grease EP 2
 MP Lithep Grease EP 2

KUBOTA TRACKED EXCAVATORS K/KH/KX/U U20-3A



COOLING SYSTEM Capacity: 3 liter (Radiator), Capacity: 0,6 liter (Reserve tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 24 months

IDLER FRONT Capacity: 0,04 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 Multifleet SCD 30	

TRACK ROLLER Capacity: 0,05 liter	
use Normal	сымате Moderate
PRODUCT RECOMMENDATION 1 Multifleet SCD 30	

TRAVEL REDUCTION UNIT Capacity: 0,33 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 500 hours

UPPER ROLLER Capacity: 0,06 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.