PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MLT MLT 627 T PERKINS 1104D-44T (STAGE IIIA) (2012 AND AFTER)

ENGINE Perkins 1104D-44T Capacity: 8,5 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agridiesel CRD+ 15W-40**	PRODUCT RECOMMENDATION 2 **Dieselfleet CD+ 15W-40**	PRODUCT RECOMMENDATION 3 **Multifleet SHPD 15W-40**
Check every 8 hours, change every 6 months/ 500 hours		

ANGLE GEARBOX Capacity: 0,6 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 80W-90**	PRODUCT RECOMMENDATION 2 **Unigear HS GL-3/GL-5 80W-90**	
Change every 1000 hours/ 12 months		

DIFFERENTIAL FRONT Capacity: 5,5 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid HT**		
Change every 6 months/ 500 hours		

DIFFERENTIAL REAR Capacity: 6,35 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid HT**		
Change every 6 months/ 500 hours		

HUB REDUCTIONS FRONT Capacity: 0,75 liter (each)		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 80W-90**	PRODUCT RECOMMENDATION 2 **Unigear HS GL-3/GL-5 80W-90**	
Change every 6 months/ 500 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MLT MLT 627 T PERKINS 1104D-44T (STAGE IIIA) (2012 AND AFTER)

HUB REDUCTIONS REAR
Capacity: 0,75 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 6 months/ 500 hours

TRANSMISSION HYDROSTATIC
Capacity: 16,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Almirol		

Change every 1000 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 128 liter, Capacity: 98 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 1000 hours/ 12 months

COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367