MANITOU MANISCOPIC MRT MRT 1432 M SERIES E2 PERKINS 1104C-44T (<- 411048)



ENGINE Perkins 1104C-44T Capacity: 7,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours/ 3 months

DIFFERENTIAL FRONT Capacity: 11 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Charle avant 350 hours shangs av	and 1000 hours / 12 months		

Check every 250 hours, change every 1000 hours/ 12 months

DIFFERENTIAL REAR Capacity: 11 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
01 1 0501	10001 / 10 //	<u> </u>	

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT Capacity: 1,6 liter (each hub)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Check every 250 hours, change eve	ery 1000 hours/ 12 months		

HUB REDUCTIONS REAR Capacity: 1,6 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Check every 250 hours, change every 1	000 hours/ 12 months	

MANITOU MANISCOPIC MRT MRT 1432 M SERIES E2 PERKINS 1104C-44T (<- 411048)



TRANSMISSION HYDROSTATIC 2/2 Capacity: 2,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 250 hours, change every 1000 hours/ 12 months

CLIMATE
Moderate

GREASE POINTS/NIPPLES GENERAL		
	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
Caliplex HD Grease EP 2		
	PRODUCT RECOMMENDATION 2	CLIMATE Moderate PRODUCT RECOMMENDATION 2

GREASE POINTS/NIPPLES PIVOTS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

GREASE POINTS/NIPPLES TELESCOPIC BOOM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

Capacity: 25 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

MANITOU MANISCOPIC MRT MRT 1432 M SERIES E2 PERKINS 1104C-44T (<- 411048)



SWING BRAKE Capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check every 50 hours, change every 1000	hours/ 12 months	

SWING REDUCTION UNIT Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
0		·

Check every 250 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.