PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA MT 1235 CP 10°/10°

ENGINE
Capacity: 7,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**
Change every 500 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**
Change every 50 hours		

DIFFERENTIAL FRONT
Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 500 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 50 hours		

DIFFERENTIAL REAR
Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 500 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 50 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA MT 1235 CP 10°/10°

HUB REDUCTIONS FRONT
Capacity: 0,45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 50 hours

HUB REDUCTIONS REAR
Capacity: 0,45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 50 hours

TRANSMISSION
Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Almirol		

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
ATF Almirol		

Change every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA MT 1235 CP 10°/10°

HYDRAULIC SYSTEM
Capacity: 190 liter (Tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

Change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 50 hours

JIB (WITH WIELAND BEARINGS)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Q7 MP Calcep Grease WR 2	**Caliplex HD Grease EP 2**	**Q5 MP Calcep Grease EP 2**

Change every 50 hours

JIB (WITHOUT WIELAND BEARINGS)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA MT 1235 CP 10°/10°

LONGITUDINAL STABILITY ALARM DEVICE REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

PADS JIB

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q7 MP Calcep Grease WR 2	**Caliplex HD Grease EP 2**	**Q5 MP Calcep Grease EP 2**

Change every 10 hours

TILTING CORRECTOR CHASSIS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q7 MP Calcep Grease WR 2	**Caliplex HD Grease EP 2**	**Q5 MP Calcep Grease EP 2**

Change every 50 hours

COOLING SYSTEM
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

WHEEL REDUCER PIVOTS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q7 MP Calcep Grease WR 2	**Caliplex HD Grease EP 2**	**Q5 MP Calcep Grease EP 2**

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367