PRODUCT RECOMMENDATION

# MANITOU MANISCOPIC MT/MTA MT 6034T DEUTZ TD3.6 L4 (16251 ->)

**ENGINE** Deutz TD 3.6 L4
Capacity: 8,9 liter

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agrisynth LSP Ultra FE 5W-30** | **Agrisynth LSP Ultra 10W-40** | **Agrisynth MSP 10W-40** |
| *Change every 100 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Alternative, fuel sulfur level < 0,0015 % | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agrisynth LSP Ultra FE 5W-30** | **Agrisynth LSP Ultra 10W-40** | **Agrisynth MSP 10W-40** |
| *Check every 10 hours, change every 250 hours/ 3 months* | | |

**DIFFERENTIAL FRONT** Dana
Capacity: 9 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT-Plus** | | |
| *Check every 250 hours, change every 1000 hours/ 12 months* | | |

**DIFFERENTIAL REAR** Dana
Capacity: 9 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT-Plus** | | |
| *Check every 250 hours, change every 1000 hours/ 12 months* | | |

**HUB REDUCTIONS FRONT**
Capacity: 0,5 liter (each hub)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT-Plus** | | |
| *Check every 250 hours, change every 1000 hours/ 12 months* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# MANITOU MANISCOPIC MT/MTA MT 6034T DEUTZ TD3.6 L4 (16251 ->)

## HUB REDUCTIONS REAR
Capacity: 0,5 liter (each hub)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT-Plus** | | |

*Check every 250 hours, change every 1000 hours/ 12 months*

## TRANSMISSION POWERSHIFT Clark T12000 3/3
Capacity: 22,7 liter (+ cooler)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **SP Matic 2032** | **ATF Almirol** | |

*Check every 10 hours, change every 1000 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **SP Matic 2032** | **ATF Almirol** | |

*Change every 100 hours*

## HYDRAULIC SYSTEM
Capacity: 133 liter (Hydraulic system including tank)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Perlus H 46** | | |

*Check every 10 hours, change every 2000 hours/ 24 months*

## HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **SP Matic 2032** | **ATF Almirol** | |

*Check every 10 hours, change every 1000 hours/ 12 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# MANITOU MANISCOPIC MT/MTA MT 6034T DEUTZ TD3.6 L4 (16251 ->)

## GREASE POINTS/NIPPLES

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

## COOLING SYSTEM

Capacity: 16,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367