

TERBERG SWAP BODY CARRIERS BC 182

MERCEDES OM904LA STAGE 3A



ENGINE Mercedes-Benz OM904LA Stage IIIA
Capacity: 16 liter

USE	CLIMATE
Extended, fuel sulfur level > 0,8 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Armado Synth 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 12 months/ 270 hours

USE	CLIMATE
Extended, fuel sulfur level 0 - 0,3 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Armado Synth 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 900 hours/ 12 months

USE	CLIMATE
Extended, fuel sulfur level 0,3 - 0,8 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Armado Synth 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 450 hours/ 12 months

USE	CLIMATE
Normal, fuel sulfur level 0 - 0,3 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 12 months/ 700 hours

USE	CLIMATE
Normal, fuel sulfur level 0,3 - 0,8 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 12 months/ 350 hours

USE	CLIMATE
Normal, fuel sulfur level > 0,8 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 12 months/ 210 hours

USE	CLIMATE
Alternative, fuel sulfur level 0 - 0,3 %	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	

Check every 10 hours, change every 500 hours/ 12 months

TERBERG SWAP BODY CARRIERS BC 182

MERCEDES OM904LA STAGE 3A



USE		CLIMATE
Alternative, fuel sulfur level 0 - 0,3 %		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 30	
<i>Check every 10 hours, change every 500 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0 - 0,3 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Check every 10 hours, change every 500 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0 - 0,3 %		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Check every 10 hours, change every 500 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0,3 - 0,8 %		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	
<i>Check every 10 hours, change every 250 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0,3 - 0,8 %		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 30	
<i>Check every 10 hours, change every 250 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0,3 - 0,8 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Check every 10 hours, change every 250 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0,3 - 0,8 %		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Check every 10 hours, change every 250 hours/ 12 months</i>		

TERBERG SWAP BODY CARRIERS BC 182

MERCEDES OM904LA STAGE 3A



USE		CLIMATE
Alternative, fuel sulfur level > 0,8 %		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	

Check every 10 hours, change every 150 hours/ 12 months

USE		CLIMATE
Alternative, fuel sulfur level > 0,8 %		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 30	

Check every 10 hours, change every 150 hours/ 12 months

USE		CLIMATE
Alternative, fuel sulfur level > 0,8 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 150 hours/ 12 months

USE		CLIMATE
Alternative, fuel sulfur level > 0,8 %		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 150 hours/ 12 months

DIFFERENTIAL REAR Axletech 5521 SFW

Capacity: 12-15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 1000 hours, change every 12 months/ 2500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Change every 100 hours

TERBERG SWAP BODY CARRIERS BC 182

MERCEDES OM904LA STAGE 3A



HUB REDUCTIONS REAR Axletech 5521 SFW

Capacity: 2,8-3,7 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 1000 hours, change every 12 months/ 2500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Change every 100 hours

TRANSMISSION AUTOMATIC ZF 3WG161 3/3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Change every 1500 hours

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Change every 100 hours

HYDRAULIC CAB TILT SYSTEM ELECTRICALLY OPERATED

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
ATF Dexron II-D	Perlus H 46	Perlus AF 46

TERBERG SWAP BODY CARRIERS BC 182

MERCEDES OM904LA STAGE 3A



HYDRAULIC CAB TILT SYSTEM MANUALLY OPERATED

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32

Check every 10 hours, change every 2000 hours/ 24 months

POWER STEERING TRW

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES WHEEL HUBS FRONT GREASE LUBRICATED Volvo

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES WHEEL HUBS FRONT OIL LUBRICATED Volvo

Capacity: 0,4 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Multifleet SCD 30	SP Gear 5015

TERBERG SWAP BODY CARRIERS BC 182

MERCEDES OM904LA STAGE 3A

**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.