PRODUCT RECOMMENDATION

ACURA (USA / CAN) NSX NC1 NSX (CAN) (2016-2022)

ENGINE JNC1
Capacity: 7,9 liter (Service fill), Filter capacity: 0,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT Twin Motor Unit
Capacity: 2,42 liter

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 24000 km

USE		CLIMATE
First change only, severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 12000 km

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

TRANSMISSION AUTOMATIC DCT CLUTCH PART M8HF 9/1
Capacity: 2,6 liter

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 32000 km

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

TRANSMISSION AUTOMATIC DCT TRANSMISSION PART M8HF 9/1
Capacity: 4,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ACURA (USA / CAN) NSX NC1 NSX (CAN) (2016-2022)

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid Racing		

Change every 36 months

COOLING SYSTEM
Capacity: 15,5 liter

USE	CLIMATE
Flexible (on board maintenance system)	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

COOLING SYSTEM INVERTER
Capacity: 1,9 liter

USE	CLIMATE
Flexible (on board maintenance system)	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367