

ACURA (USA / CAN) RLX RLX 3.5 I-VTEC V6 HYBRID (USA) (2015-2020)

**ENGINE JNB1**

Capacity: 4,3 liter (Service fill), Filter capacity: 0,3 liter

USE

Flexible (on board maintenance system)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 0W-20****DIFFERENTIAL REAR Twin Motor Unit**

Capacity: 2,42 liter

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4036***Change every 15000 miles***USE**

Severe, first change only

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4036***Change every 7500 miles***USE**

Flexible (on board maintenance system)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4036**

ACURA (USA / CAN) RLX RLX 3.5 I-VTEC V6 HYBRID (USA) (2015-2020)



TRANSMISSION AUTOMATIC DCT 7/1

Capacity: 3,5 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 25000 miles

USE	CLIMATE
Severe, first change only	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 30000 miles

USE	CLIMATE
Flexible (on board maintenance system)	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 36 months

COOLING SYSTEM

Capacity: 7,9 liter (Service fill)

USE	CLIMATE
Flexible (on board maintenance system)	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

COOLING SYSTEM INVERTER

Capacity: 1,23 liter

USE	CLIMATE
Flexible (on board maintenance system)	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

ACURA (USA / CAN) RLX RLX 3.5 I-VTEC V6 HYBRID (USA) (2015-2020)



AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 455-505 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.