

ALFA ROMEO (EU) 147 937 147 1.6 TS (77 KW) (2000-2010)

**ENGINE AR 37203**

Capacity: 4,4 liter, Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Emperol Racing 10W-60	Emperol 10W-40

Check every 500 km, change every 20000 km/ 12 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Duranza LSP 5W-30	Asyntho 5W-30

Check every 500 km, change every 20000 km/ 12 months

TRANSAXLE MANUAL 5/1

Capacity: 2,01 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 5015	SP Gear 1071

Check every 80000 km/ 48 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,52 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Check every 500 km, change every 60000 km/ 24 months

POWER STEERING

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Check every 20000 km/ 12 months

ALFA ROMEO (EU) 147 937 147 1.6 TS (77 KW) (2000-2010)**COOLING SYSTEM**

Capacity: 6,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 500 km, change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.