

ALFA ROMEO (EU) SPIDER 939 SPIDER 3.2 JTS V6 Q4 (2006-2008)



ENGINE 939A000
Capacity: 5,4 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

Change every 30000 km

DIFFERENTIAL REAR
Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Syngear 75W-90

Change every 120000 km

TRANSAXLE AUTOMATIC Aisin Warner AF 40-6 6/1
Capacity: 6,1 liter (Dry fill), Capacity: 3,3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Check every 30000 km

TRANSAXLE MANUAL 6/1
Capacity: 2,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear 75W-90

Check every 30000 km

TRANSFERBOX
Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Syngear 75W-90

Change every 120000 km

ALFA ROMEO (EU) SPIDER 939 SPIDER 3.2 JTS V6 Q4(2006-2008)



HYDRAULIC SYSTEM (ROOF) ELECTRONIC/HYDRAULIC

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
<i>Check every 30000 km</i>		

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
<i>Check every 30000 km, change every 60000 km</i>		

POWER STEERING

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
<i>Check every 30000 km</i>		

COOLING SYSTEM

Capacity: 10,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
<i>Check every 30000 km</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.