

**ENGINE**

Capacity: 3,5 liter, Filter capacity: 0,5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Specialsynth MSP 5W-40****PRODUCT RECOMMENDATION 2****Emperol 5W-40****PRODUCT RECOMMENDATION 3****Emperol 10W-40***Change every 7500 km/ 12 months***TRANSAXLE MANUAL 4/1****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****HYDRAULIC BRAKE SYSTEM****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 24 months***POWER STEERING****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Fluid 3013***Check every 12 months/ 30000 km***COOLING SYSTEM**

Capacity: 6,5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant -38 Organic NF***Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.