NISSAN (EU) QASHQAI J10 QASHQAI 1.5 DCI (2010-2014)



| ENGINE K9K Capacity: 4,6 liter, Filter capacity: 0,2 liter | | | | |
|--|--------------------------|--------------------------|--|--|
| use Normal | | CLIMATE | | |
| | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Helar SP LL-03 5W-30 | Presteza MSP 5W-30 | Meganza MSP 5W-30 | | |
| Change every 20000 km/ 12 month | s | | | |
| USE | | CLIMATE | | |
| Severe | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Helar SP LL-03 5W-30 | Presteza MSP 5W-30 | Meganza MSP 5W-30 | | |
| Change every 10000 km/ 6 months | | , | | |

| TRANSAXLE MANUAL RS6F94R 6/1 Capacity: 2 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Gear 5015 | |
| Check every 15000 km/ 12 months | ' |

| HYDRAULIC BRAKE/CLUTCH SYSTEM ABS | | | | |
|-----------------------------------|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | | |
| | | | | |

Check every 15000 km/12 months, change every 30000 km/24 months

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

NISSAN (EU) QASHQAI J10 QASHQAI 1.5 DCI (2010-2014)



| COOLING SYSTEM Capacity: 7-7,4 liter | | |
|--------------------------------------|----------------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 16 | Coolant SP 14+ | |
| Check every 15000 km/ 12 months, of | change every 60000 km/ 48 months | |
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 16 | Coolant SP 14+ | |
| Change every 90000 km/ 60 months | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.