

FIAT-TRATTORI 90 100-90, 100-90 DT (1984-1993)

**ENGINE**

Capacity: 13,7 liter, Filter capacity: 1,6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	

Change every 200 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Change every 200 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Change every 200 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

*Change every 200 hours***DIFFERENTIAL FRONT (4x4)**

Capacity: 5,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

*Check every 400 hours, change every 1600 hours***DIFFERENTIAL REAR/HYDRAULIC SYSTEM**

Capacity: 44,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Change every 1600 hours

FIAT-TRATTORI 90 100-90, 100-90 DT (1984-1993)



HUB REDUCTIONS FRONT (4x4)

Capacity: 1,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Check every 400 hours, change every 1600 hours

TRANSMISSION MANUAL 15/3

Capacity: 11,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Check every 400 hours, change every 1600 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

POWER STEERING

Capacity: 1,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Change every 800 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	

FIAT-TRATTORI 90 100-90, 100-90 DT (1984-1993)



GREASE POINTS/NIPPLES KING PINS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	

Check every 400 hours

GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	

Check every 400 hours

COOLING SYSTEM

Capacity: 21 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 1600 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.