## AMMANN ARTICULATED TANDEM ROLLERS AV AV 95NK YANMAR S/N 0800 ->



ENGINE Yanmar 4TNE106 Capacity: 12,5 liter		
JSE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Check every 10 hours, change every 250	hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 250	hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Check every 10 hours, change every 250	hours	
JSE		CLIMATE
Normal		Cold
		55.2
PRODUCT RECOMMENDATION 1		
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W	hours	
PRODUCT RECOMMENDATION 1  Multifleet SCD 10W  Check every 10 hours, change every 250  JSE	hours	CLIMATE
PRODUCT RECOMMENDATION 1  Multifleet SCD 10W  Check every 10 hours, change every 250  USE  Initial service	hours	
PRODUCT RECOMMENDATION 1  Multifleet SCD 10W  Check every 10 hours, change every 250  USE  Initial service  PRODUCT RECOMMENDATION 1	hours	CLIMATE
PRODUCT RECOMMENDATION 1  Multifleet SCD 10W  Check every 10 hours, change every 250  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40	hours	CLIMATE
Multifleet SCD 10W  Check every 10 hours, change every 250  use Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours	hours	climate Tropical
PRODUCT RECOMMENDATION 1  Multifleet SCD 10W  Check every 10 hours, change every 250  JSE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  JSE	hours	climate Tropical
Multifleet SCD 10W  Check every 10 hours, change every 250  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial service	hours	climate Tropical
PRODUCT RECOMMENDATION 1  Multifleet SCD 10W  Check every 10 hours, change every 250  USE  Initial Service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  Initial Service  PRODUCT RECOMMENDATION 1	hours	climate Tropical
Multifleet SCD 10W  Check every 10 hours, change every 250  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 30	hours	climate Tropical
Multifleet SCD 10W  Check every 10 hours, change every 250  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours	hours	CLIMATE Tropical  CLIMATE Mediterranean
Multifleet SCD 10W  Check every 10 hours, change every 250  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours	hours	CLIMATE Tropical  CLIMATE Mediterranean  CLIMATE
Multifleet SCD 10W  Check every 10 hours, change every 250  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours	PRODUCT RECOMMENDATION 2	CLIMATE Tropical  CLIMATE Mediterranean

## AMMANN ARTICULATED TANDEM ROLLERS AV AV 95NK YANMAR S/N 0800 ->



use Initial service	climate Cold
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 50 hours	'

HYDRAULIC SYSTEM Capacity: 110 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Check every 10 hours, change ever	ry 1000 hours/ 12 months	
USE		CLIMATE

Biodegradable oil Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

Moderate

Check every 10 hours, change every 1000 hours/12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM		O. WATE
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

## AMMANN ARTICULATED TANDEM ROLLERS AV AV 95NK YANMAR S/N 0800 ->



VIBRATORY DRUM FRONT Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP Synth 220	Abacot MEP 220	
Change every 500 hours/ 12 months		

VIBRATORY DRUM REAR Capacity: 8 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP Synth 220	Abacot MEP 220	

Change every 500 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.