

# ATLAS GMBH WHEELED EXCAVATORS

## 1204 129M301365 ->



### ENGINE

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 50 hours*

### DIFFERENTIAL HUB REDUCTIONS

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
<b>Gearlube Racing 75W-140</b>		

*Change every 1000 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 1000 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1		
<b>Gearlube Racing 75W-140</b>		

*Change every 500 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 500 hours*

# ATLAS GMBH WHEELED EXCAVATORS

## 1204 129M301365 ->



### TRANSFERBOX

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Change every 1000 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 1000 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Change every 500 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 500 hours*

### HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20***Change every 3000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Change every 3000 hours*

# ATLAS GMBH WHEELED EXCAVATORS

## 1204 129M301365 ->



### GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

### COOLING SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 11***Change every 2000 hours*

### SWING RING GEAR TEETH

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Compound OGL EP 0/1**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*