ATLAS GMBH WHEELED EXCAVATORS 1404 143M301863 ->



ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Change every 500 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL HUB REDUCTIONS	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 1000 hours	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours	
USE	CLIMATE
Initial service	Tropical
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 500 hours	
USE	CLIMATE
Initial service	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 500 hours	

ATLAS GMBH WHEELED EXCAVATORS 1404 143M301863 ->



TRANSFERBOX	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 1000 hours	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours	
USE	CLIMATE
Initial service	Tropical
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 500 hours	
USE	CLIMATE
Initial service	 Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 500 hours	
HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 20W-20	
Change every 3000 hours	
USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Change every 3000 hours

ATLAS GMBH WHEELED EXCAVATORS 1404 143M301863 ->



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		
01 000001	•	*

Change every 2000 hours

SWING RING GEAR TEETH		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Compound OGL EP 0/1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.