

# ATLET LOW LIFTER ERGO XLL 200



## TRANSMISSION

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

## PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140***Change every 800 hours*

## USE

Normal

## CLIMATE

Arctic

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 800 hours*

## USE

Severe

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

## PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140***Change every 500 hours*

## USE

Severe

## CLIMATE

Arctic

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 500 hours*

# ATLET LOW LIFTER ERGO XLL 200



## HYDRAULIC SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Perlus H 32</b>       |  |  |

*Change every 800 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Perlus H 15</b>       |  |  |

*Change every 800 hours*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Perlus H 32</b>       |  |  |

*Change every 500 hours*

| USE    | CLIMATE |
|--------|---------|
| Severe | Arctic  |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Perlus H 15</b>       |  |  |

*Change every 500 hours*

## GREASE POINTS/NIPPLES LIFT CHAIN

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

|                               |  |  |
|-------------------------------|--|--|
| PRODUCT RECOMMENDATION 1      |  |  |
| <b>Industrial Chain Spray</b> |  |  |

## GREASE POINTS/NIPPLES MAST BEARINGS

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

|                          |                                 |                              |
|--------------------------|---------------------------------|------------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

**ATLET LOW LIFTER ERGO XLL 200****GREASE POINTS/NIPPLES MAST CHAINS**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

**GREASE POINTS/NIPPLES STEERING CHAINS**

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

**GREASE POINTS/NIPPLES WHEEL BEARINGS**

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*