AUSA FORKLIFT TRUCKS C 350 H (4X2) KUBOTA V3300-E2B (2005 AND AFTER)



| USE | | CLIMATE |
|-----------------------------------|--------------------------|--------------------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | Multifleet SHPD 20W-50 |
| Change every 250 hours/ 12 months | 3 | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 |
| Change every 250 hours/ 12 months | | |
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | Multifleet SHPD 20W-50 |
| Change every 50 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 |
| Change every 50 hours | | , |
| | | |
| DIFFERENTIAL FRONT | | |
| Capacity: 6 liter | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| | I | |

| Change | every | 50 hours |
|--------|-------|----------|
| | | |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

USE

Initial service

Check every 40 hours, change every 12 months/ 500 hours

CLIMATE

Moderate

AUSA FORKLIFT TRUCKS C 350 H (4X2) KUBOTA V3300-E2B (2005 AND AFTER)



| HUB REDUCTIONS FRONT Capacity: 0,7 liter (each hub) | | |
|--|-------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |
| Check every 40 hours, change every 12 n | nonths/ 500 hours | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |
| Change every 50 hours | | |

| TRANSFERBOX Capacity: 3,25 liter | | |
|-------------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 40 hours, change every 12 months/ 500 hours

| use Normal | | CLIMATE |
|-----------------------------------|--------------------------|----------|
| | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus H 46 | Perlus AF 46 | |
| Check every 40 hours, change ever | ry 1000 hours | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus H 46 | Perlus AF 46 | |
| Change every 50 hours | | ' |

AUSA FORKLIFT TRUCKS C 350 H (4X2) KUBOTA V3300-E2B (2005 AND AFTER)



| HYDRAULIC SYSTEM BRAKING & INCHING Capacity: 1 liter | | | |
|--|---------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Kroontrak CVT 10W-40 | Agrifluid Synth XHP Ultra | Kroontrak MTH 10W-30 | |
| Check every 40 hours, change ever | v 24 months/ 1000 hours | | |

Check every 40 hours, change every 24 months/ 1000 hours

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

| COOLING SYSTEM Capacity: 13 liter | | | |
|------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |
| Check every 40 hours, change every | / 24 months | | |

Check every 40 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.