

**AUSA MULTITASK B200H (2010 AND AFTER)**

**ENGINE** Volkswagen TDI 2.0  
Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Helar SP LL-03 5W-30**

*Check every 10 hours, change every 300 hours/ 12 months*

**HYDRAULIC SYSTEM**

Capacity: 45 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Perlus H 68**

*Check every 40 hours, change every 900 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

PRODUCT RECOMMENDATION 2

**Perlus H 46**

*Check every 40 hours, change every 900 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 32**

PRODUCT RECOMMENDATION 2

**Perlus H 32**

*Check every 40 hours, change every 900 hours*

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

*Change every 24 months/ 900 hours*

**AUSA MULTITASK B200H (2010 AND AFTER)****AUTOMATIC LUBRICATION SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Grease EP 0**

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Gear Grease EP 00/000****GREASE POINTS/NIPPLES AXLE FRONT**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2***Check every 40 hours***GREASE POINTS/NIPPLES AXLE REAR**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2***Check every 40 hours***GREASE POINTS/NIPPLES OTHERS**

We are unable to give a standard recommendation for this component. Please contact our service department.

**COOLING SYSTEM**

Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 12***Check every 10 hours, change every 24 months/ 1800 hours*

**AUSA MULTITASK B200H (2010 AND AFTER)****HIGH PRESSURE PUMP**

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 600 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 50 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*