

# AUSA MULTITASK BD202HL (2011 AND AFTER)



**ENGINE** Kubota V1505  
Capacity: 5,75 liter

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Mediterranean                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SHPD 20W-50</b> |

*Check every 10 hours, change every 200 hours/ 12 months*

| USE                         |                             | CLIMATE                     |
|-----------------------------|-----------------------------|-----------------------------|
| Normal                      |                             | Moderate                    |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

*Check every 10 hours, change every 200 hours/ 12 months*

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Initial service               |                               | Mediterranean                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SHPD 20W-50</b> |

*Change every 50 hours*

| USE                         |                             | CLIMATE                     |
|-----------------------------|-----------------------------|-----------------------------|
| Initial service             |                             | Moderate                    |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

*Change every 50 hours*

**DIFFERENTIAL FRONT**  
Capacity: 3,5 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Check every 40 hours, change every 12 months/ 1000 hours*

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Initial service             |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 50 hours*

# AUSA MULTITASK BD202HL (2011 AND AFTER)



## DIFFERENTIAL REAR

Capacity: 3,3 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Check every 40 hours, change every 12 months/ 1000 hours

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Initial service             |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Change every 50 hours

## HUB REDUCTIONS REAR

Capacity: 0,25 liter (each)

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Check every 40 hours, change every 12 months/ 1000 hours

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Initial service             |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Change every 50 hours

## TRANSFERBOX Compen

Capacity: 1,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## HYDRAULIC SYSTEM

Capacity: 38 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |          |

Check every 40 hours, change every 1000 hours

## GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

# AUSA MULTITASK BD202HL (2011 AND AFTER)


**COOLING SYSTEM**

Capacity: 5 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

## PRODUCT RECOMMENDATION 2

**Coolant -26**

*Check every 40 hours, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*