

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40D MK 7 (6X6) MERCEDES-BENZ OM501LA (STAGE 3B)



ENGINE Mercedes-Benz OM501LA
Capacity: 32 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Armado Synth 10W-40

Change every 500 hours

DIFFERENTIAL FRONT (WET DISC BRAKES) 25A6HA
Capacity: 47 liter (Dry fill), Capacity: 46 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT (WET DISC BRAKES) Meritor 25M6HA

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL MIDDLE (WET DISC BRAKES) 25A6HB
Capacity: 47 liter (Dry fill), Capacity: 46 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL MIDDLE (WET DISC BRAKES) Meritor 25M6HB

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR (WET DISC BRAKES) 25U6HA
Capacity: 47 liter (Dry fill), Capacity: 46 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR (WET DISC BRAKES) Meritor 25U6HA

We are unable to give a standard recommendation for this component. Please contact our service department.

FINAL DRIVES
Capacity: 4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSFERBOX VGR 17000
Capacity: 4,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
SP Matic 2032

Change every 2000 hours

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40D MK 7 (6X6) MERCEDES-BENZ OM501LA (STAGE 3B)

**TRANSMISSION** Allison 4500R ORS 6/1

Capacity: 40 liter (Dry fill), Capacity: 34 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 2000 hours***HYDRAULIC SYSTEM**

Capacity: 185 liter (Hydraulic system including tank), Capacity: 177,6 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus H 32

PRODUCT RECOMMENDATION 3

Perlus H 68*Change every 4000 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Grease EP 1

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Gear Grease EP 0**COOLING SYSTEM**

Capacity: 33,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION

**BELL EQUIPMENT ARTICULATED DUMP
TRUCKS B-C-D-E SERIES B40D MK 7 (6X6)
MERCEDES-BENZ OM501LA (STAGE 3B)**



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.