

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B50D MK VI (6X6) MERCEDES-BENZ OM502LA (TIER 2/3)

**ENGINE** Mercedes-Benz OM502LA

Capacity: 38 liter (Dry fill), Capacity: 30 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrisynth LSP 10W-40****PRODUCT RECOMMENDATION 2****Armado Synth 10W-40***Change every 500 hours***DIFFERENTIAL FRONT (WET DISC BRAKES) 27A10HA**

Capacity: 70 liter (Dry fill), Capacity: 68 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus***Check every 500 hours, change every 1000 hours***DIFFERENTIAL MIDDLE (WET DISC BRAKES) 27A10HB**

Capacity: 70 liter (Dry fill), Capacity: 68 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus***Check every 500 hours, change every 1000 hours***DIFFERENTIAL REAR (WET DISC BRAKES) 27A10HA**

Capacity: 70 liter (Dry fill), Capacity: 68 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus***Check every 500 hours, change every 1000 hours***FINAL DRIVES**

Capacity: 7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus**

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B50D MK VI (6X6) MERCEDES-BENZ OM502LA (TIER 2/3)

**TRANSFERBOX** VGR 17100

Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

*Change every 2000 hours***TRANSMISSION** Allison 4600R ORS 6/1

Capacity: 40 liter (Dry fill), Capacity: 34 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

*Check every 500 hours, change every 1000 hours***HYDRAULIC SYSTEM**

Capacity: 268,5 liter (Hydraulic system including tank), Capacity: 256 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 32	Perlus H 68

*Change every 4000 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

PRODUCT RECOMMENDATION

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B50D MK VI (6X6) MERCEDES-BENZ OM502LA (TIER 2/3)



COOLING SYSTEM

Capacity: 33,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.