BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T17D (6X6) MERCEDES-BENZ OM906LA (TIER 2)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Armado Synth 10W-40	

Change every 500 hours

DRIVE AXLES Bell Capacity: 40 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Unigear LS GL-3/GL-5 85W-140	
Check every 500 hours, change every 1000 hours	
USE	CLIMATE
Normal	Moderate

Normal Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Moderate

Check every 500 hours, change every 1000 hours

FINAL DRIVES Capacity: 2 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Unigear LS GL-3/GL-5 85W-140	

Check every 1000 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 1000 hours, change every 2000 hours		

Check every 1000 hours, change every 2000 hours

BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T17D (6X6) MERCEDES-BENZ OM906LA (TIER 2)



TRANSFERBOX VGR 13100 Capacity: 4,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Change every 2000 hours	·

TRANSMISSION ZF 6HP592C 6/1 Capacity: 30 liter (Dry fill), Capacity: 10-15 liter (Service fill)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Change every 2000 hours	'	

HYDRAULIC SYSTEM Capacity: 85 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46
Change every 4000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	Perlus H 32
Change every 4000 hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T17D (6X6) MERCEDES-BENZ OM906LA (TIER 2)



COOLING SYSTEM Capacity: 28 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.