

# BELL EQUIPMENT WHEELED LOADERS L F1204C FLEXILOADER/FLEXIPILER MERCEDES-BENZ OM364A



**ENGINE** Mercedes-Benz OM364A  
Capacity: 10 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 250 hours/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 250 hours/ 6 months*

**DIFFERENTIAL FRONT** Bell  
Capacity: 28 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Unigear LS GL-3/GL-5 85W-140</b>		

*Change every 3000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 3000 hours*

**DIFFERENTIAL REAR** Bell  
Capacity: 28 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Unigear LS GL-3/GL-5 85W-140</b>		

*Change every 3000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 3000 hours*

# BELL EQUIPMENT WHEELED LOADERS L F1204C FLEXILOADER/FLEXIPILER MERCEDES-BENZ OM364A

**FINAL DRIVES**

Capacity: 4 liter (each)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Unigear LS GL-3/GL-5 85W-140***Change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 1000 hours***TRANSMISSION** Clark 24000 4/3

Capacity: 25 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 2

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 3

**Kroontrak MTH 10W-30***Change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W**

PRODUCT RECOMMENDATION 2

**SP Matic 2032**

PRODUCT RECOMMENDATION 3

**ATF Dexron II-D***Change every 1000 hours***HYDRAULIC SYSTEM**

Capacity: 125 liter (Hydraulic system including tank), Capacity: 100 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

PRODUCT RECOMMENDATION 2

**Multifleet SCD 10W**

PRODUCT RECOMMENDATION 3

**ATF-F (Ford)***Change every 3000 hours*

# BELL EQUIPMENT WHEELED LOADERS L F1204C FLEXILOADER/FLEXIPILER MERCEDES-BENZ OM364A



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 22 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*