

# BELL EQUIPMENT RIGID TRACTORS & HAULERS 2256A JOHN DEERE 6068HF250



**ENGINE** John Deere 6068 HF250  
Capacity: 19 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3     |
|-----------------------------|-----------------------------|------------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

*Change every 250 hours/ 6 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3     |
|-----------------------------|-----------------------------|------------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

*Change every 100 hours*

**DIFFERENTIAL REAR** Bell 13T  
Capacity: 36 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Change every 1000 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Change every 1000 hours*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Change every 100 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Change every 100 hours*

# BELL EQUIPMENT RIGID TRACTORS & HAULERS 2256A JOHN DEERE 6068HF250



**TRANSMISSION** Allison MD 3060P 5/1  
Capacity: 8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

*Change every 1000 hours*

## HYDRAULIC SYSTEM

Capacity: 140 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

## COOLING SYSTEM

Capacity: 22 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*